

Serrofinations platometer castaniceler Motschulsky

## Flexibility

Roll to location, set working height. Respond to changing needs.

## flexiroller specifications

	Flexiroller IWB	Flexiroller ID60	Flexiroller ID120
Description		Wheeled trolley with electric lift suitable for displays up to 60kg	Wheeled trolley with electric lift suitable for displays up to 120kg
Lift mechanism	Single actuator drives twin lifting columns via belt	Single actuator drives twin lifting columns via belt	Dual synchronised actuators
Folding Laptop tray	Optional extra	Included	Included
Audio	Optional 25W RMS (2.1)	None	None
Handling	Tubular full height handle at each end	None (handles provided on display)	Handle attached to chassis frame
Wheels	4 x heavy duty castors (2 braked) rated 65kg each		
Dimensions	Wheelbase options: 2420mm 2120mm, 1820mm Width: 605mm.	Wheelbase: 1820mm Width: 605mm	Wheelbase: 2120mm Width: 605mm
Lifting stroke	710mm	710mm	650mm
Lifting Capacity	60kg	60kg	160kg



Unit 25, 632 Clayton Road, Clayton South VIC 3169, Australia Tel: 1800 246 808; 03 9808 0988 Email: sales@twotouch.com www.twotouch.com